



# FTC-B255FS

BENCH-TOP TYPE CUTTING MACHINE



# BENCH-TOP TYPE CUTTING MACHINE

- Silent operation is realized by the tough machine body.
- Simple design with handleability.
- Many kinds of sample fixing jig can be used on the stage.



FTC-B255FS

ITEM		SPECIFICATIONS
MODEL		MANUAL TYPE
		FTC-B255FS
Design / Structure		Benchtop Type (Base: Aluminum Casting / Cover: Steel Sheeting with Hard Acrylic Window)
Safety Mechanism	Motor	As the "Doors Interlock" contact is down(when the front door opened), main motor shaft and coolant circulation stop instantaneously.
Doors	Front	Up-and-Down Open Door with Hard Acrylic Windows
	Left Hand Side	Small Slide Door for inserting long specimen
Max Available Sample Size	Cylindrical	In case Ø230mm Cutting Wheel: MaxØ60mm In case Ø255mm Cutting Wheel: MaxØ70mm
Cutting Wheel	Dimensions	Outer Dia.: Ø230/255mm x Inner Dia.: Ø31.75mm x T1.2mm
	Flange	Outer Dia.: Ø60mm
	Rotary Speed	3420rpm-60Hz / 2850rpm-50Hz
	Main Motor	3HP / 2.2KW / AC3P Induction Motor
Movable Sample Stage	Structure	Fixed Type
	Dimensions	W225 x 220mm with 4 T-slots (X direction: 6 slots each with 10mm width) for fixing various vice and jig
Sample Fixing Vise		Various kinds of Vise and Fixing Jigs attachable on Stage (OPTION)
Special Sample Fixing Jig		
Cooling Section	Structure	Separate Type / Double Tank Type (with Steel Mesh Filter)
	Cut Powder Separator	Magnet Separator (OPTION)
	Coolant Tank Capacity	25L
	Circulation Pump	1/4HP
	Coolant Capacity	30L/min
	Water Nozzle	for Cutting Sample: 2pcs / for Cleaning Chamber: 1pc
Inner Illumination		LED Light: 1pc
Machine Dimensions		W650 x D700 x H405mm
Machine Weight		120kg
Cooling Tank	Cooling Device Dimensions	W410 x D340 x H565mm (OPTION)
	Cooling Device Weight	18kg
Power Supply		3P-AC200~240V / 50Hz, 60Hz (OPTION: 3P-AC380V)
Standard Accessories		Cutting Wheel: Ø255mm x 2pcs Wrench: 2pcs / Coolant: 1L x 1btl



## FUTURE-TECH CORP.

**HEAD OFFICE :** TALKPIER KAWASAKI BLDG., NO. 5-1, 3-CHOME, FUJISAKI, KAWASAKI-KU, KAWASAKI, KANAGAWA, 210-0804 JAPAN  
TEL +81-44-270-5789 FAX +81-44-266-6779  
E-mail: info@ft-hardness.com  
URL: http://www.ft-hardness.com

**EUROPEAN REPRESENTATIVE OFFICE :**  
VIA LOMELLINA 33, 20090 BUCCINASCO, MILAN, ITALY  
TEL/FAX: +39-02-30912227  
E-mail: cantoni.ft@gmail.com

**F.T.T.CO.,LTD. / ASIA PRODUCTS SUPPORT CENTER :**  
200 THOSAPOL BLDG., 3RD FL., UNIT C,  
RATCHADAPISEK RD., HUAYKWANG,  
BANGKOK 10310, THAILAND  
TEL: +66-2-692-7667~8 FAX: +66-2-692-7669  
E-mail: siripong@ft-hardness.com

Agent :



**JCSS 0228**  
We are based on ISO 9001:2015 (ISO/IEC 17025) as accredited standards, and accredited by JCSS who manages the recognition scheme according to ISO/IEC 17011.  
IA Japan (accreditation organization who has managed JCSS) who is signatory to the Mutual Recognition Arrangement (MRA) of International Laboratory Accreditation Cooperation (ILAC) and Asia Pacific Laboratory Accreditation Cooperation (APLAC).  
We are accredited as MRA Calibration Laboratory of JCSS.  
Our accreditation number is JCSS 0228.

